


Perceptor 15 Kiosk



Customer Display*



MSR Card Reader*



VESA Mount Compatible

* Optional configuration





SPECIFICATIONS

	Perceptor 15W	Perceptor 15A
PROCESSOR	Intel Quad Core Celeron J1900 2.0 GHz, up to 2.42 GHz	Rockchip RK3288 Quad Core 1.8 GHz
SYSTEM MEMORY	4 GB SO-DIMM DDR3L RAM, up to 8 GB	2 GB RAM
STORAGE DEVICE	Removable 128 GB 2.5" SATA SSD (up to 256 GB)	16 GB eMMC

DISPLAY

SIZE/RESOLUTION	15.6" TFT LCD (LED backlight) / 1920 x 1080 pixels (widescreen)
BRIGHTNESS	220 cd/m ²
TOUCH SCREEN PANEL	Projected capacitive touch (multi-touch)

I/O INTERFACE

USB PORT	Side: 1 x USB 2.0 Back: 3 x USB 2.0, 1 x USB 3.0	Side: 1 x USB 2.0 Back: 4 x USB 2.0
SERIAL PORT	3 x RJ50	1 x RJ 50
AUDIO PORT	1 x 2 W speaker	
ETHERNET PORT	1 x RJ45 100M/1000M Gigabit LAN	
CASH DRAWER PORT	1 x RJ12 (24 V)	

OPERATING SYSTEM

WINDOWS / ANDROID	Windows POSReady 7 / 7 Pro / 10 IoT / 10 Pro	Android 7.1
-------------------	--	-------------

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT (Standard base version)	Landscape: 386 (W) x 395 (H) x 205 (D) mm 6.5 kg Portrait: 250 (W) x 465 (H) x 205 (D) mm 6.5 kg
CHASSIS MATERIAL	Plastic & die-cast aluminium
TEMPERATURE	Operating: 0°C to 45°C Storage: -10°C to 70°C
HUMIDITY	10% to 90% (non-condensing)
POWER CONSUMPTION	24 V / 2.5 A, external power adaptor, 100-240 V, 50/60 Hz, 60 W

MODEL OPTIONS

INTEGRATED CARD READERS	3-track MSR, RFID (13.56 MHz)
CUSTOMER DISPLAY	15.6" TFT LCD
WIRELESS LAN & BLUETOOTH	Dual-band Wi-Fi 802.11 a/b/g/n/ac 2.4 GHz & 5 GHz, Bluetooth 4.2 (Optional) (Included)

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
sales@senortech.com.au

SENIOR
TOUCH SCREEN SOLUTIONS

Quality. Safety. Versatility.